



Technical Bulletin #2008-02

To: All Grand-Am Competitors
 Effective: Immediately, unless otherwise noted.
 From: Grand-Am
 Date: May 9, 2008

GT Regulations

Section 2-20.12 Aluminum bolt-on external front wheel wicker is permitted. (This is the replacement of previous carbon part. Available from Porsche Motorsports North America)

KONI Challenge Series

Section 8-3 (Changes in Red)

Chevrolet Cobalt SS/SC (2.0) 2005	4.45:1	17.0	2725	Tire size: 225/45/17. Allowed: modify rear sway bar mount for adjustment, relocate lower rear shock mount ½ inch forward for wheel clearance, HHR power steering unit , #CCS609 hood, #CCS610 deck lid, #CCS611 spoiler, #CCS608 fascia, front knuckle conversion #CCC606, Spherical end for lower control arm included in kit, spherical bearings on rear axle, bolt-on rear caliper bracket, rear wheel bearing conversion . Allowed light weight doors and fenders for 2008. Must use 2006 OEM brakes. Maximum RPM. 6700. Must use OEM ECU. Maximum boost 15 psi.
Honda Civic Si 2008 2DR and 4DR	5.02:1	17.0	2500	Tire size 225/45/17. Allowed: K20A JDM engine, exhaust header, TSX brakes. Must use OEM ECU.
Mazda MX-5 Miata 2006	4.875:1	17.0	2350	Tire size 225/45/17. Allowed #0000-06-5150-KT air intake, #0000-06-5407 header. Must use #NFY2-R1-82XE-XX hard top. May use aftermarket ECU. Camshaft is free. #0000-01-5207 Mazda Speed Piston kit. Throttle pedal # C19-09-07A
Mazda RX-8 2004	5.12:1	17.9	2650	Tire size 225/45/17 RPM limit TBD. Mazda Speed aero #QSEA-50-02—X1, QSEA-51-96Z and QSEA-70-900-X1 are allowed. Allowed exhaust header. Allowed oil cooler vent in trunk. May use aftermarket ECU. Throttle pedal must be converted to manual actuation for installation of aftermarket ECU.
Scion TC	4.235:1	17.0	2500	Tire size 225/45/17. Allowed: TRD Supercharger kit, exhaust header #DC-SHR4402, lightweight hatch, lightweight hood # SC04BMN1SCFH, replacement roof #KO60660FC, Camry brakes. Must use OEM ECU with AEM #30-1050 supercharger controller. Maximum boost 12 psi.
Subaru Legacy Spec B Sedan 2007 (2.5) 6 speed	4.11:1	17.0	3100	Tire size 225/45/17. Must run stock exhaust with muffler, stock air box with stock air filter, Must use OEM factory ECU. Maximum RPM 6500, Maximum boost 13 psi. May use 2008 fascias.